

## 1 Grade/Product Name

HM9450F (EX<sub>2</sub>) For blown films with paper like quality, suitable for counter bags, carried bags and w / aping film, exellent processing.

## 2 Features

High molar mass film grade, good stiffness and tenacity

## 3 Applications

- ♦ Blown
- ♦ Film

## 4 Additives

- ♦ Antioxidant/Process stabilizer
- ♦ Lubricant (processing aid)/ acid scavenge

Test/Composition	Method	Unit	TypicalValue
Density	ISO 1183	g/cm <sup>3</sup>	0.949
Fish Eye Note	Internal	note	3
FRR 21.6/5			29
MFR 190°/21.6	ISO1133	g/10min	8.0
MFR190°/5	ISO1133	g/10min	0.28

Notes:

- ♦ Test specimen from compression moulded sheet at 23°C.
- ♦ FRR values are statistical and calculated by dividing MFR values.
- ♦ Notch Impact Test specimen from compressed moulded sheet 23°C and The data quoted are average values

**VİRA PROSHOT KİMYA SANAYİ VE DİŐ TİCARET LİMİTED ŐİRKETİ**  
Adres : ZÜHTÜPAŐA MAH. ŐEFİKBEY SK. NO: 3 Kadıköy, İstanbul – Türkiye Post Code : 34724